



WINDOW ELECTRIC

design **Beatrice De Sanctis**

MATERIAL:

Heating body and handle in ultra-thin painted carbon steel.

FIXING KIT:

Brackets, airvent, hexagonal tool, plugs and screws for mounting suitable for use on compact or hollow brick, installation notice.
The kit is certified from TÜV in compliance with VDI 6036-class 4.

FEATURES:

The exclusive design of the Window towel warmer combines aesthetics and functionality.

The heated handle can be extracted, acting as support for warming the towels. The opening and closing of the handle are manually operated. Window has been designed to offer maximum comfort of use by differentiating the temperature of the handle from that of the body.

The temperature of the handle is kept lower than that of the radiator body, so to allow a safe grip without sacrificing the maximum heat output provided by the radiator body at the normal operating temperatures of the heating system.

PACKAGING:

The radiator is protected with a film in polyethylene and cardboard box. Use and maintenance notice included.

PAINTING PROCESS:

Painted with ecological epoxy. (Certificate DIN 55900-1,-2). Thermal outputs certified in accredited laboratories in compliance with European norm EN442.

COLOURS:

Radiators and accessories: standard white R01 colour.

**EUROPEAN
WARRANTY**

Electrical resistors: CLASS 2

Minimum class protection: IP 44

Seasonal energy efficiency η_s : $\geq 38\%$

Control: Power unit + Digital chrono thermostat in radio frequency

Cable length:

- With EU schuko socket: 1000 mm

CERTIFICATES




AWARDS



HOW TO PLACE ELECTRIC RADIATORS

The national rules on installing electrical equipment in the bathroom must be scrupulously respected. The electric radiators must be always installed outside zone 1 and 2.




In particular the electric switch and control elements must be mandatorily located in zone 3, in order that no electrical control center is accessible to anyone using the shower or bath.



BICOLOR

BODY

FRAME





F30
WHITE SAND

F36
TERRA

BODY

FRAME





T20
WHITE GREY

T17
ACAI MATT

BODY

FRAME








F25
QUARTZ DUST

F23
SPARKLING GREY

Available color combinations.

CORDIVARI
DESIGN



WINDOW ELECTRIC

Art. Nr.	Height		Width	Thermal output	Weight
	H [mm]		L [mm]	Watt	Kg
DIGITAL CHRONOTHERMOSTAT KIT IN RADIOFREQUENCY SCHUKO PLUG 230V 50HZ CLASS 2					
3581420002002	495		1100	454	18

Art. Nr. are referred to WHITE R01 colour version.

WINDOW BICOLOR ELECTRIC

Art. Nr.	Colour		Height	Width	Thermal output	Weight
	BODY	FRAME	H [mm]	L [mm]	Watt	Kg
DIGITAL CHRONOTHERMOSTAT KIT IN RADIOFREQUENCY SCHUKO PLUG 230V 50HZ CLASS 2						
3581420002004	F30	F36	495	1100	454	18
3581420002005	T20	T17				
3581420002006	F25	F23				